

Paving Stone Specifications

Western Interlock paving stones are made from a low moisture concrete mixture. They are made under high pressure and high frequency vibration, producing a very dense stone, low in water absorption (less than 5%) and with a high PSI rating (above 8000 psi). They are designed to meet or exceed ASTM 936 and ASTM C-67-73 (freeze/thaw) specifications.

| Stone | Pcs/Sq Foot | Lbs/pcs | Pcs/ Layer | Layers/ Pallet | Pcs/ Pallet | Sq Ft/ Pallet | Lbs/ Pallet | Stock | Non-Stock |
|---|--------------------|----------------|-------------------|-----------------------|--------------------|----------------------|--------------------|--------------|------------------|
| Alpine Stone Large Square | .85 | 38 | 9 | 8 | 72 | 84.7 | 2714 | • | |
| Alpine Stone Large Rec | 1.28 | 26 | 12 | 8 | 96 | 74.88 | 2471 | • | |
| Alpine Stone Med Square | 1.92 | 20 | 20 | 8 | 160 | 83.2 | 2746 | • | |
| Alpine Stone Small Rec | 3.84 | 9 | 40 | 8 | 320 | 83.2 | 2746 | • | |
| Alpine Rotundo Stone | n/a | various | 12 | 4 | 48 | n/a | | • | |
| Alpine Rotundo Single Stone | 1.05 | | 12 | 8 | 96 | n/a | | | |
| Arena Stone | 1 | 28 | 12 | 9 | 108 | 108 | 2970 | • | |
| Camino Stone Large Rec | 2.42 | 11 | 30 | 9 | 270 | 111.5 | 3067 | • | |
| Camino Stone Square | 3.65 | 8 | 42 | 9 | 378 | 103.5 | 2888 | • | |
| Camino Stone Small Rec | 4.76 | 6 | 49 | 9 | 441 | 92.6 | 2515 | • | |
| Capital Stone - 80mm | 1.78 | 21 | 20 | 7 | 140 | 78.65 | 3453 | | • |
| City Square | 4.09 | 8 | 42 | 9 | 378 | 92.42 | 3024 | • | |
| VS-5™ Drain Pave | 2.35 | 16 | 20 | 7 | 120 | 52 | 1920 | • | |
| Holland Stone | 4.56 | 6 | 54 | 9 | 486 | 106.6 | 2931 | • | |
| Holland Stone - Roca | 4.56 | 6 | 54 | 9 | 486 | 106.6 | 2931 | • | |
| Inter Stone | 3.6 | 8 | 40 | 9 | 360 | 100 | 2750 | | • |
| Inter Stone - 80mm | 3.6 | 10 | 40 | 7 | 280 | 77.7 | 2877 | | • |
| Octo Stone | 3.6 | 8 | 40 | 9 | 360 | 100 | 2750 | • | |
| Octo Stone Edger | 4.88 | 6 | 50 | 9 | 450 | 83 | 2268 | • | |
| Park Stone | 2.29 | 12 | 24 | 9 | 216 | 94.1 | 2588 | • | |
| Park Stone - Cobble | 2.29 | 12 | 24 | 9 | 216 | 94.1 | 2588 | • | |
| Park Stone - Granite | 2.29 | 12 | 24 | 9 | 216 | 94.1 | 2588 | | |
| Park Stone - Roca | 2.29 | 12 | 24 | 9 | 216 | 94.1 | 2588 | • | |
| Plaza Stone | 1.53 | 18 | 16 | 9 | 144 | 94.1 | 2588 | • | |
| Plaza Stone - Cobble | 1.53 | 18 | 16 | 9 | 144 | 94.1 | 2588 | • | |
| Plaza Stone - Granite | 1.53 | 18 | 18 | 8 | 144 | 94.1 | 2588 | | |
| Plaza Stone - Roca | 1.53 | 18 | 16 | 9 | 144 | 94.1 | 2588 | • | |
| Rotundo Stone | n/a | various | 37 | 9 | 333 | 103.5 | 2850 | • | |
| Rotundo Stone - Roca | n/a | various | 37 | 9 | 333 | 103.5 | 2850 | | • |
| Cobble Slimline Large Rec - 40mm | 3.24 | 6 | 30 | 12 | 360 | 111 | 2011 | • | |
| Cobble Slimline Square - 40mm | 4.88 | 4 | 48 | 12 | 576 | 118 | 2143 | • | |
| Holland Slimline | 4.51 | 4 | 45 | 12 | 540 | 119.7 | 2127 | • | |
| Turf Stone | .38 | 73 | 4 | 5 | 20 | 52 | 1456 | • | |
| Village Stone | 3.5 | 8 | 40 | 9 | 360 | 103 | 2920 | | • |
| Village Stone - 80mm | 3.5 | 10 | 40 | 7 | 280 | 80 | 2960 | | • |
| Village Stone Edger | 4.4 | 7 | 45 | 9 | 405 | 92 | 2350 | | • |
| Village Stone Edger - 80mm | 4.4 | 8 | 45 | 7 | 315 | 71.5 | 2650 | | • |